

PRIMESTICK-AR



SINGLE COMPONENT ACRYLIC BASED PIGMENTED PRIMER

hahne PrimeStick-AR is a single-component, water-based pigmented primer specially designed for sealing the porosity of concrete and masonry surfaces and improving adhesion of subsequent elastomeric waterproofing coatings. It provides excellent penetration and bonding to absorbent as well as selected non-absorbent substrates, forming a smooth, uniform and matt primed surface.



PRODUCT INFORMATION

Area of Applications

- Priming of concrete and masonry surfaces prior to application of acrylic waterproofing membrane.
- Exterior RCC surfaces, including sloping roofs.
- Masonry walls and facades.

Features and Benefits

- Single-component, water-based pigmented primer.
- Excellent penetration into porous concrete and masonry substrates.
- Excellent bonding to absorbent and non-absorbent surfaces.
- Seals substrate porosity and helps reduce uneven absorption of the subsequent coating.
- Easy application by brush or roller.
- Suitable as an adhesion-promoting primer for compatible elastomeric waterproofing coatings.

Consumption

- Approx. 0.2–0.25 L/m².

*Coverage may vary depending on surface condition, temperature, applicator skill, surface porosity and substrate quality.

TECHNICAL SPECIFICATIONS

Property	Test Method	Result
Density	ASTM D 1475-2013	1.3 – 1.4 g/cc
Non-Volatile Content (Solid Content)	ASTM D 1644-2001	25 ± 2 %

APPLICATION PROCEDURE

Surface Preparation

- The substrate must be dry, clean and free from grease, tar, oil, dust and loose particles.
- Repair or remove weak, loose or poorly bonded areas and ensure the substrate is suitable for priming.

Application

- Stir **hahne PrimeStick-AR** thoroughly before application.
- Apply a thin, uniform coat by brush or suitable spray equipment over the prepared substrate.
- Allow the primer to dry, or until the solvent has evaporated and the primer is dry.
- Apply **hahne AR-SEAL** or **hahne AR-SEAL PREMIUM** waterproofing coating directly over the primed substrate after the primer has dried.

PACKAGING, STORAGE AND SAFETY

Packaging

- **hahne PrimeStick-AR** is supplied in 25 kg buckets.

Storage and Shelf Life

- Store in unopened, original, sealed and dry condition.
- Keep away from direct heat, flames and other ignition sources.
- Shelf life is 12 months from the date of manufacture when stored under recommended conditions.

Cleaning

- Clean tools used for application with a suitable standard solvent before the primer hardens.

Safety Instructions

- Highly inflammable; keep away from fire, sparks and heat.
- Use in adequately ventilated areas and avoid prolonged exposure in enclosed spaces.
- Wear suitable hand gloves, safety shoes and safety goggles while handling and applying the product.
- In case of contact with eyes or mouth, wash immediately with plenty of clean water and seek medical attention.
- Refer to the relevant Safety Data Sheet before use.

DISCLAIMER: The information and application guidelines provided by the company and its representatives are intended solely as a general reference. Users are strongly encouraged to conduct their own tests and trials to verify the product's suitability for their specific requirements before proceeding with full-scale use. As the identification of underlying issues, the quality of other materials and the workmanship on-site are beyond our control, we cannot offer any express or implied guarantees regarding the results. The company disclaims any liability for damages or unsatisfactory outcomes that may arise from the use of our products.